



CUMMINS INC.
Columbus, IN 47201
Marine Performance Curves

Basic Engine Model
QSM11-300 HO

Engine Configuration
D353021MX03

Curve Number:
M-20051


CPL Code:
8590

Date:
12-May-10

Displacement: **10.8 liter** [661 in³]
Bore: **125 mm** [4.92 in]
Stroke: **147 mm** [5.79 in]
Fuel System: **CELECT**
Cylinders: **6**

Rated Power: **220 kw** [295 bhp, 300 mhp]
Rated Speed: **1800 rpm**
Rating Type: **High Output**
Aspiration: **Turbocharged / Jacket Water Aftercooled**

CERTIFIED: This diesel engine complies with or is certified to the following agencies requirements:
IMO Tier I - Tier 1 (One) NOx requirements of International Maritime Organization (IMO), MARPOL 73/78 Annex VI, Regulation 13
EPA Tier 2 - Model year requirements of the EPA marine regulation (40CFR94)



Speed	Full Throttle- Power		Full Throttle- Torque		Fuel Cons.- Prop. Curve 2.7 Exp.	
	rpm	kw (hp)	N-m (ft-lb)		L/hr (gal/hr)	
1840	220	(295)	1142	(842)		
1800	220	(295)	1167	(861)	55.2	(14.6)
1700	222	(298)	1247	(920)	46.7	(12.3)
1600	223	(299)	1329	(980)	40.3	(10.6)
1500	221	(297)	1410	(1040)	34.4	(9.1)
1400	219	(293)	1491	(1100)	28.4	(7.5)
1300	214	(287)	1573	(1160)	23.4	(6.2)
1200	198	(265)	1573	(1160)	19.0	(5.0)

* Cummins Full Throttle Requirements:

- Engine achieves or exceeds rated rpm at full throttle under any steady operating condition
- Engines in variable displacement boats (such as pushboats, tugboats, net dragners, etc.) achieve no less than 100 rpm below rated speed at full throttle during a dead push or bollard pull
- Engine achieves or exceeds rated rpm when accelerating from idle to full throttle

Rated Conditions: Ratings are based upon ISO 15550 reference conditions; air pressure of 100 kPa [29.612 in Hg], air temperature 25deg. C [77 deg. F] and 30% relative humidity. Power is in accordance with IMCI procedure. Member NMMA. Unless otherwise specified, tolerance on all values is +/-5%.

Full Throttle curve represents power at the crankshaft for mature gross engine performance corrected in accordance with ISO 15550. Propeller Curve represents approximate power demand from a typical propeller. Propeller Shaft Power is approximately 3% less than rated crankshaft power after typical reverse/reduction gear losses and may vary depending on the type of gear or propulsion system used.

Fuel Consumption is based on fuel of 35 deg. API gravity at 16 deg. C [60 deg. F] having LHV of 42,780 kJ/kg [18390 Btu/lb] and weighing 838.9 g/liter [7.001 lb/U.S. gal].

High Output (HO): Intended for use in variable load applications where full power is limited to one hour out of every eight hours of operation. Also, reduced power must be at or below 200 rpm of the maximum rated rpm. This power rating is for pleasure/non-revenue generating applications that operate 500 hours per year or less.

CHIEF ENGINEER

Propulsion Marine Engine Performance Data

Curve No. M-20051
DS : 3075
CPL : 8590
DATE: 12-May-10

General Engine Data

Engine Model	QSM11-300 HO
Rating Type	High Output
Rated Engine Power	220 [295]
Rated Engine Speed	1800
Rated Power Production Tolerance	5
Rated Engine Torque	1167 [861]
Peak Engine Torque @ 1300 rpm.....	1573 [1160]
Brake Mean Effective Pressure	1355 [197]
Indicated Mean Effective Pressure.....	1534 [223]
Maximum Allowable Engine Speed	1860
Maximum Torque Capacity from Front of Crank ²	847 [625]
Compression Ratio	15.9:1
Piston Speed	8.8 [1736]
Firing Order	1-5-3-6-2-4
Weight (Dry) - Engine Only - Average	1118 [2464]
Weight (Dry) - Engine With Heat Exchanger System - Average.....	1184 [2610]
Weight Tolerance (Dry) Engine Only	N.A.

Governor Settings

High Speed Governor Break Point.....	1840
Minimum Idle Speed Setting	600
Normal Idle Speed Variation	10
High Idle Speed Range Minimum	1840
Maximum	1860

Noise and Vibration

Average Noise Level - Top	(Idle)..	80
	(Rated)	95
Average Noise Level - Right Side	(Idle)..	80
	(Rated)	95
Average Noise Level - Left Side	(Idle)..	80
	(Rated)	95
Average Noise Level - Front	(Idle)..	80
	(Rated)	95

Fuel System¹

Avg. Fuel Consumption - ISO 8178 E3 Standard Test Cycle	39.4 [10.4]
Fuel Consumption at Rated Speed	55.2 [14.6]
Approximate Fuel Flow to Pump	219.6 [58.0]
Maximum Allowable Fuel Supply to Pump Temperature	60.0 [140]
Approximate Fuel Flow Return to Tank	164.3 [43.4]
Approximate Fuel Return to Tank Temperature	71.2 [160]
Maximum Heat Rejection to Drain Fuel	2.6 [149]
Fuel Transfer Pump Pressure Range.....	N.A.
Fuel Pressure - Pump Out/Rail . Mechanical Gauge	1103 [160]
INSITE Reading	N.A.

TBD= To Be Determined

N/A = Not Applicable

N.A. = Not Available

- ¹ Unless otherwise specified, all data is at rated power conditions and can vary ± 5%.
- ² No rear loads can be applied when the FPTO is fully loaded. Max PTO torque is contingent on torsional analysis results for the specific drive system. Consult Installation Direction Booklet for Limitations.
- ³ Heat rejection to coolant values are based on 50% water/50% ethylene glycol mix and do NOT include fouling factors. If sourcing your own cooler, a service fouling factor should be applied according to the cooler manufacturer's recommendation.
- ⁴ Consult option notes for flow specifications of optional Cummins seawater pumps, if applicable.
- ⁵ May not be at rated load and speed. Maximum heat rejection may occur at other than rated conditions.

CUMMINS ENGINE COMPANY, INC
 COLUMBUS, INDIANA

All Data is Subject to Change Without Notice - Consult the following Cummins intranet site for most recent data:

<http://cmdmarine.com/>

Propulsion Marine Engine Performance Data

Curve No. **M-20051**
DS : **3075**
CPL : **8590**
DATE: **12-May-10**

Air System¹

Intake Manifold Pressure	kPa [in Hg]	118 [35]
Intake Air Flow	l/sec [cfm]	288 [611]
Heat Rejection to Ambient	kW [Btu/min]	17 [966]

Exhaust System¹

Exhaust Gas Flow	l/sec [cfm]	621 [1315]
Exhaust Gas Temperature (Turbine Out)	°C [°F]	385 [725]
Exhaust Gas Temperature (Manifold)	°C [°F]	526 [978]

Emissions (in accordance with ISO 8178 Cycle E3)

NOx (Oxides of Nitrogen)	g/kw-hr [g/hp-hr]	6.28 [4.68]
HC (Hydrocarbons)	g/kw-hr [g/hp-hr]	0.26 [0.19]
CO (Carbon Monoxide)	g/kw-hr [g/hp-hr]	0.58 [0.43]
PM (Particulate Matter)	g/kw-hr [g/hp-hr]	0.17 [0.13]

Cooling System¹

Sea Water Pump Specifications	MAB 0.08.17-07/16/2001	
Pressure Cap Rating (With Heat Exchanger Option)	kPa [psi]	103 [15]

Engines without Low Temperature Aftercooling (LTA)

Sea Water Aftercooled Engine (SWAC)

Coolant Flow to Engine Heat Exchanger	l/min [gal/min]	151 [39.9]
Standard Thermostat Operating Range (Start to Open)	°C [°F]	71 [160]
Standard Thermostat Operating Range (Full Open)	°C [°F]	80 [175]
Heat Rejection to Engine Coolant ³	kW [Btu/min]	223 [12700]

Engines with Low Temperature Aftercooling (LTA)

Single Loop LTA

Coolant Flow to Cooler (with blocked open thermostat).....	l/min [gal/min]	170 [45]
LTA Thermostat Operating Range (Start to Open)	°C [°F]	66 [150]
LTA Thermostat Operating Range (Full Open)	°C [°F]	80 [175]
Heat Rejection to Engine Coolant ³	kW [Btu/min]	181 [10288]
Maximum Coolant Inlet Temperature from LTA Cooler.....	°C [°F]	54 [130]

TBD= To Be Determined

N/A = Not Applicable

N.A. = Not Available

- ¹ Unless otherwise specified, all data is at rated power conditions and can vary ± 5%.
- ² No rear loads can be applied when the FPTO is fully loaded. Max PTO torque is contingent on torsional analysis results for the specific drive system. Consult Installation Direction Booklet for Limitations.
- ³ Heat rejection to coolant values are based on 50% water/50% ethylene glycol mix and do NOT include fouling factors. If sourcing your own cooler, a service fouling factor should be applied according to the cooler manufacturer's recommendation.
- ⁴ Consult option notes for flow specifications of optional Cummins seawater pumps, if applicable.
- ⁵ May not be at rated load and speed. Maximum heat rejection may occur at other than rated conditions.

CUMMINS ENGINE COMPANY, INC
 COLUMBUS, INDIANA

All Data is Subject to Change Without Notice - Consult the following Cummins intranet site for most recent data:

<http://cmdmarine.com/>